



SYNMAR LIVIUS 5W-30 | S100001 V24-1501

Description

Synmar Livius 5W-30 is a fully synthetic MID SAPS engine oil. This lubricant is specifically suitable for diesel and gasoline engines. Moreover this engine oil meets the VW 504.00 – 507.00 norm, also called VW Longlife III.

Application

Synmar Livius 5W-30, fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. The Synmar Livius 5W-30 also contributes to the extension of the lifetime of particle filters. Due to its special composition it is possible to apply this product for the VW 504.00/507.00 requirements, in practice also called VW Longlife III.

Performance Level

ACEA C3
API SN
BMW Longlife-04
MB 229.31/229.51/229.52
OV0401547
Porsche C30
VW 504.00/507.00

Typicals

Density at 15 °C, kg/l	0,851
Viscosity -30 °C, mPa.s	6140
Viscosity 40 °C, mm ² /s	68,90
Viscosity 100 °C, mm ² /s	12,00
Viscosity Index	172
Flash Point COC, °C	232
Pour Point, °C	-42
Total Base Number, mgKOH/g	6,7
Sulphate Ash, %	0,67

The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this overview is composed with the most possible care, Synmar does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.

SYNMAR B.V.

Albert Schweitzerstraat 7, 7131 PG Lichtenvoorde, The Netherlands
T: +31 (0) 33 303 3044 | M: info@synmar.nl