



SYNMAR REMUS 5W-40 | S100002 V24-3009

Description

Synmar Remus 5W-40 is a fully synthetic MID SAPS motor oil suitable for both gasoline and diesel engines. This oil is specifically suitable for EURO 4 cars of Opel, Mercedes Benz with soot filters. This oil is also suitable for all VAG group engines with normal drain intervals.

Application

The Synmar Remus 5W-40 is suitable for use in petrol and diesel engines, with or without turbo-charging. Moreover the Synmar Remus 5W-40 is also very suitable for passenger car diesel engines with pump-injector-unit. This product meets the requirements of several OEM's and thus has a wide application.

Performance Level

ACEA C3	GM Dexos 2
API SN/CF	MB 229.51/229.31/226.5
BMW Longlife-04	Porsche A40
Fiat 9.55535-GH2/S2/T2	Renault RN0700/RN0710
Ford WSS-M2C917-A	VW 502.00/505.01

Typicals

Density at 15 °C, kg/l	0,849
Viscosity -30 °C, mPa.s	6320
Viscosity 40 °C, mm ² /s	78,80
Viscosity 100 °C, mm ² /s	13,40
Viscosity Index	174
Flash Point COC, °C	230
Pour Point, °C	-39
Total Base Number, mgKOH/g	7,4
Sulphate Ash, %	0,78

The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this overview is composed with the most possible care, Synmar does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.