



SYNMAR QUINTUS 5W-30 | S100004 V24-3009

Description

The Synmar Quintus 5W-30 is a fully synthetic motor oil based on high quality solvent refined mineral and synthetic base oils. By adding a well balanced choice of additives the following properties are obtained:

- a high and stable viscosity index
- a fast cold start
- a strong resistance against oxidation
- a good detergency and dispersion
- a safe lubrication film at high temperatures
- a strong protection against wear, corrosion and foaming

Application

The Synmar Quintus 5W-30 is an all-round motor oil which is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.

Performance Level

ACEA A3/B4
API SN/CF
MB 229.5/229.3/226.5

Opel GM-LL-A-025/GM-LL-B-025
VW 502.00/505.00
Renault RN0710/RN700

Typicals

Density at 15 °C, kg/l	0,856
Viscosity -30 °C, mPa.s	5780
Viscosity 40 °C, mm ² /s	67,40
Viscosity 100 °C, mm ² /s	10,80
Viscosity Index	151
Flash Point COC, °C	223
Pour Point, °C	-39
Total Base Number, mgKOH/g	10,2
Sulphate Ash, %	1,26

The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this overview is composed with the most possible care, Synmar does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.

SYNMAR B.V.

Albert Schweitzerstraat 7, 7131 PG Lichtenvoorde, The Netherlands
T: +31 (0) 33 303 3044 | M: info@synmar.nl