



SYNMAR QUINTUS 5W-40 | S100005 V24-3009

Description

The Synmar Quintus 5W-40 is a fully synthetic motor oil based on high quality solvent refined mineral and synthetic base oils. By adding a well balanced choice of additives the following properties are obtained:

- a high and stable viscosity index
- a fast cold start
- a strong resistance against oxidation
- a good detergency and dispersion
- a safe lubrication film at high temperatures
- a strong protection against wear, corrosion and foaming

Application

The Synmar Quintus 5W-40 is an all-round motor oil which is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.

Performance Level

ACEA A3/B4	MB229.5/229.3
API SN/CF	Porsche A40
GM/Opel GM-LL-A-025/GM-LL-B-025	Renault RN0710
VAG 502.00/505.00	

Typicals

Density at 15 °C, kg/l	0,853
Viscosity -30 °C, mPa.s	6100
Viscosity 40 °C, mm ² /s	80,30
Viscosity 100 °C, mm ² /s	13,10
Viscosity Index	165
Flash Point COC, °C	220
Pour Point, °C	-39
Total Base Number, mgKOH/g	10,2
Sulphate Ash, %	1,26

The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this overview is composed with the most possible care, Synmar does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.

SYNMAR B.V.

Albert Schweitzerstraat 7, 7131 PG Lichtenvoorde, The Netherlands
T: +31 (0) 33 303 3044 | M: info@synmar.nl