



SYNMAR AURELIUS 0W-30 | S100006 V24-3009

Description

The Synmar Aurelius 0W-30 is a fully synthetic, fuel economy, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils to which advanced additives are added to obtain the following properties:

- a lower fuel consumption
- suitable for modern catalysts
- a very fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

The Aurelius 0W-30 is a fully synthetic, fuel economy, "mid SAPS" motor oil which is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. Due to its low SAPS content this product can be applied in vehicles with modern three way catalysts and diesel particle filters.

Performance Level

ACEA C2
PSA B71 2290/2312
Fiat 9.55535-GS1/DS1

Typicals

Density at 15 °C, kg/l	0,842
Viscosity -30 °C, mPa.s	5920
Viscosity 40 °C, mm ² /s	55,10
Viscosity 100 °C, mm ² /s	9,8
Viscosity Index	165
Flash Point COC, °C	230
Pour Point, °C	-51
Total Base Number, mgKOH/g	6,2
Sulphate Ash, %	0,54

The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this overview is composed with the most possible care, Synmar does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.